

# GENERAL SHELTERS SPECIFICATION SHEET

<p><b>Building Size</b> <u>14' x 30'</u></p> <p><b>Roof Style</b> <u>PICK ONE</u></p> <p><b>Porch</b> <u>4' x 4' Corner Style</u></p> <p><b>Floor:</b>                  Skids: Double Skids                  Insulation: None                  Joists: 2" x 8" on 16" Center                  Decking: 3/4" Subfloor</p> <p><b>Floor Covering:</b>                  1/8" Tile: <u>VCT Beige Taupe</u>                  26oz. Carpet: <u>Loft Only</u></p> <p><b>Exterior:</b>                  Walls: 8' Walls                  Studs: 2" x 4" x 91.5" on 16" Center                  Bottom Plate: 2" x 4"                  Top Plate: Double 2" x 4"                  Sheathing: <u>House Wrap Only</u>                  Insulation: R-15 Fiberglass                  Siding: 29 ga. _____                  Window Trim: 29 ga. _____</p> <p><b>Interior:</b>                  Studs: 2" x 4" x 91.5" on 16" Center                  Covering: Paneling: _____                  Cabinets: Color: <u>Toast Oak</u>                  Trim: All Cedar                  Counter Top: <u>Roll Back (Sandy Topaz)</u>                  Closets: 1 rod and shelf                  Pantry: _____                  Misc.: _____                  Mirror: 1 <u>24" x 36" Bathroom centered under light</u></p> <p><b>Roof:</b>                  Truss: Engineered on 24" Center                  Ceiling: <u>5/16" Sea Spray Sheetrock</u>                  Insulation: R-19 Fiberglass                  Decking: Radiant 7/16" OSB w/ Felt Paper                  Roofing: 26ga. _____                  Rake Trim: 26ga. _____  <b>Anchor Straps:</b> 4 Skid Attached - Field Installed</p> <p><b>HVAC:</b>                  A/C - Heating: <u>18,000 Heat/Cool Thru Wall Unit</u></p> <p><b>SPECIAL ITEMS:</b></p>	<p><b>Doors:</b>                  Exterior Door: 1 <u>36"x80" Fiberglass Out Swing</u>                  Exterior Door: _____                  Door Insert: <u>1/2 Glass</u>                  Door Insert: _____                  Door Color: _____                  Interior Doors 1 <u>24" Dbl. Flat Panel Stain Grade</u>                  1 <u>32" Flat Panel Stain Grade</u>                  _____                  _____                  _____</p> <p><b>Windows:</b>                  Window Type: <u>Vinyl</u>                  1 <u>30"x 36" Low E Insulated</u>                  1 <u>18"x36" Low E Insulated</u>                  2 <u>72"x66" Low E Insulated</u>                  _____                  _____                  Window Color: _____                  Shutter Color: _____</p> <p><b>Electrical:</b>                  Load Center: 1 200 Amp Exterior Panel                  Wiring: #12 Romex                  Receptacles: 12 15 amp. Brown                  GFI Receptacles: 2 GFI Interior 1 Exterior GFI                  Lighting: 2 Ceiling Fan                  Lighting: 2 LED Disk                  Lighting: 1 Galvanized                  Porch Light 1 LED Disk                  Misc.: 1 Smoke Detector                  Exhaust Fans: 1 110 CFM Exhaust Fan</p> <p><b>Plumbing:</b>                  Bathroom #1: <u>60" Shower w/seat Kit</u>                  Bathroom #2: _____                  Water Closets: Elongated                  Lavatory: Porcelain Sink                  Water Heater: In Line                  Faucet Type: Residential Brass Body                  Sink: Stainless Single Bowl</p> <p><b>Appliances:</b>                  18 cu.ft. Refrigerator 1 #N/A                  Full Size Range 1 Stainless                  Microwave w/ vent 1 #N/A                  _____ 0                  _____ 0                  _____ 0</p>
--	--

Model: Corner Suite 420 sq.ft.

Dealer: \_\_\_\_\_

Approval: \_\_\_\_\_

Date: \_\_\_\_\_

bus: 936-598-3389

fax: 936-598-7717

www: generalshelters.com

