

# GENERAL SHELTERS SPECIFICATION SHEET

<b>Building Size</b>	<u>18' x 64'</u>	<b>Doors:</b>	
<b>Roof Style</b>	<u>Gable w/ 9" and Raised Roof</u>	Exterior Door:	2 <u>36"x80" Fiberglass Out Swing</u>
<b>Porch</b>	<u>Special Cedar around Door &amp; Window</u>	Exterior Door:	
<b>Floor:</b>		Door Insert:	<u>1/2 Glass Star</u>
Skids: Double Skids		Door Insert:	<u>Full Glass Star</u>
Insulation: R-19 Fiberglass w/ Vapor Barrier		Door Color:	
Joists: 2" x 8" on 16" Center		Interior Doors	1 <u>22" A/C Flat Panel Stain Grade</u>
Decking: 3/4" Subfloor			3 <u>32" Pocket Flat Panel Stain Grade</u>
<b>Floor Covering:</b>			1 <u>30" Pocket Flat Panel Stain Grade</u>
1/8" Tile: <u>Pick a tile</u>			2 <u>32" Flat Panel Stain Grade</u>
26oz. Carpet: <u>None</u>			1 <u>24" Pocket Flat Panel Stain Grade</u>
			1 <u>60" Bifold Flat Panel Stain Grade</u>
			1 <u>24" Bifold Flat Panel Stain Grade</u>
<b>Exterior:</b>		<b>Windows:</b>	
Walls: 8' Walls		Window Type:	<u>Vinyl</u>
Studs: 2" x 4" x 91.5" on 16" Center			1 <u>30"x 36" Low E Insulated</u>
Bottom Plate: 2" x 4"			4 <u>36"x 66" Low E Insulated</u>
Top Plate: Double 2" x 4"			3 <u>36"x24" Low E Insulated Fixed</u>
Sheathing: <u>7/16" OSB w/ House Wrap</u>			2 <u>30"x 54" Low E Insulated</u>
Insulation: R-15 Fiberglass			1 <u>18"x36" Low E Insulated</u>
Siding: 29 ga. _____ <b>w/cedar in</b>		Window Color:	_____
Window Trim: 29 ga. _____ <b>Door &amp; Window</b>		Shutter Color:	_____
	<b>Area</b>		
<b>Interior:</b>		<b>Electrical:</b>	
Studs: 2" x 4" x 91.5" on 16" Center		Load Center:	1 200 Amp Exterior Panel
Covering: Paneling: _____		Wiring:	#12 Romex
Cabinets: Color: _____		Receptacles:	20 15 amp. Brown
Trim: All Cedar		GFI Receptacles:	8 GFI Interior      2 Exterior GFI
Counter Top: _____		Lighting:	3 Ceiling Fan
Closets: 2 rod and shelf		Lighting:	11 LED Disk
Pantry: 1 24"x84" Cabinet		Lighting:	3 Galvanized
Misc.: 2 30" Cabinet above washer /dryr		Porch Light	2 Galvanized
Mirror: 1 48" x 36" Bathroom		Misc.:	3 Smoke Detector
Mirror: 1 24" x 36" Bathroom		Exhaust Fans:	2 110 CFM Exhaust Fan
<u>centered under light</u>			
<b>Roof:</b>		<b>Plumbing:</b>	
Truss: Engineered on 24" Center		Bathroom #1:	1 <u>60" Shower w/seat Kit</u>
Ceiling: <u>29ga. Galvalume</u>		Bathroom #2:	1 <u>60" Tub /Shower Kit</u>
Insulation: <u>Blow-In R-30 Cellulose Insulation</u>		Water Closets:	Elongated
Decking: Radiant 7/16" OSB w/ Felt Paper		Lavatory:	Porcelain Sink
Roofing: 26ga. _____		Water Heater:	In Line
Rake Trim: 26ga. _____		Faucet Type:	Residential Brass Body
<b>Anchor Straps:</b> 7 <u>Skid Attached - Field Installed</u>		Sink:	Stainless Double Bowl
		<b>Appliances:</b>	
<b>HVAC:</b>		25.3 cu.ft. Refrigerator (36")	1 Stainless
A/C - Heating: <u>3 Ton Residential Unit</u>		Full Size Range	1 Stainless
		Microwave w/ vent	1 #N/A
<b>SPECIAL ITEMS:</b> 1 cedar between window 60"x54		Dishwasher	1 White
window and door only		Washer	1 #N/A
		Dryer	1 #N/A



Model: Dreamcatcher II      1152 sq.ft.

Dealer: \_\_\_\_\_

Approval: \_\_\_\_\_

Date: \_\_\_\_\_

bus: 936-598-3389  
 fax: 936-598-7717  
 www: generalshelters.com